



Performance

- 30 to 250 litres/min flow
- 1.06 to 7.06 CFM flow



- Green drive technology – energy efficient motors low power consumption
- Specially formulated diaphragm material for extended life
- Due to no wearing parts no reduction in performance
- Robust and compact construction – weatherproof
- Easy to service with competitively priced spares kit
- Suited to intermittent or continuous duty applications
- Used by original equipment manufacturers of NSF certified residential sewage treatment systems
- UL and CE approved



Envir-o Accessories



Disk diffuser



Coarse bubble diffuser




Tube diffuser




Envirosure alarm

Application Ideas




Performance/Technical




Model no.	Performance		Noise Level dBA	Power Consumption w
	Flow (l/min) @pressure (bar)	Flow (CFM) @pressure (bar)		
ET30	30.0 @ 0.15	1.06 @ 0.15	40.0	25
ET40	40.0 @ 0.15	1.41 @ 0.15	40.0	30
ET60	60.0 @ 0.15	2.12 @ 0.15	40.0	55
ET80	80.0 @ 0.15	2.83 @ 0.15	40.0	75
ET100	100.0 @ 0.10	3.53 @ 0.10	45.0	80
ET120	120.0 @ 0.10	4.24 @ 0.10	45.0	90
ET150	150.0 @ 0.20	5.30 @ 0.20	45.0	150
ET200	200.0 @ 0.20	7.06 @ 0.20	46.0	220

ET30, ET40, ET150 & ET200



ET60, ET80, ET100 & ET120



Model no.	Dimensions mm (inch)				Weight kg
	A	B	C	D	
ET30	208 (8.18)	150 (5.90)	178 (7.00)	14 (0.55)	4.0
ET40	220 (8.66)	155 (6.10)	190 (7.48)	14 (0.55)	4.3
ET60	203 (7.99)	165 (6.49)	153 (6.02)	18 (0.70)	6.0
ET80	210 (8.26)	185 (7.28)	171 (6.73)	18 (0.70)	7.0
ET100	238 (9.37)	196 (7.71)	177 (6.96)	18 (0.70)	8.5
ET120	265 (10.43)	215 (8.36)	198 (7.79)	18 (0.70)	9.5
ET150	256 (10.07)	200 (7.87)	222 (8.74)	18 (0.70)	9.0
ET200	256 (10.07)	200 (7.87)	222 (8.74)	18 (0.70)	9.0

Connections

ET30, ET40 - Plain, horizontal, connection 14.0mm(0.55") OD also supplied with screw in barbed connector 10mm(0.39") OD

ET60, ET80, ET100 and **ET120** - Plain, horizontal, connection 18.0mm(0.71") OD also supplied with screw in barbed connector 12.0mm(0.47") OD

ET150, ET200 - Plain, horizontal, connection 18.0mm(0.71") OD

Distributed by:



Please note - it is important that you ensure the motor specification stated and the range of materials offered in the pump are compatible with the performance, environmental limitations and chemical resistance requirements of the application.

For further information or details of our extensive range of pumps, contact our technical sales office who will be pleased to help you select the most suitable pump for your application.